



PLACE BACKFLOW TO HINGED END FOR MAXIMUM CLEARANCE.

C IS THE MINIMUM CLEARANCE REQUIRED FOR HINGED MODELS.

MODELS	H	C	H	C	H	C	H	C
GS-2 (CUSTOM) HINGED 10"W x 24"H x 30"L	16"	3 5/8"	18"	4 3/4"	20"	6 1/8"	22"	7 3/4"
GS-3 HINGED 10"W x 24"H x 40"L	16"	2 3/4"	18"	3 1/2"	20"	4 1/2"	22"	5 1/2"
GS-3.3 HINGED 16"W x 30"H x 30"L	22"	7 5/8"	24"	9 1/2"	26"	11 5/8"	28"	14 1/4"
GS-3.5 HINGED 16"W x 30"H x 40"L	22"	5 1/2"	24"	6 3/4"	26"	8 1/8"	28"	9 3/4"
GS-4 HINGED 16"W x 30"H x 46"L	22"	5 3/8"	24"	6 1/4"	26"	7 1/2"	28"	8 3/4"

BACKFLOW PREVENTION DEVICE ENCLOSURES
 3831 E. GROVE STREET
 PHOENIX, ARIZONA 85040 (602) 426-1002

CLEARANCE CHART

SCALE: 3/4" = 1'
 DETAIL NO.
 BPD1-070908-1
 REV. 0