

GuardShack™ ClamShell



Never any sharp corners or edges; always powder coated to exacting standards for lasting durability. Pioneering beautiful design safe for children and pedestrians.

Most 2½"-8" backflows fit into these enclosures and are fully accessible by one person.

Model	Type	Internal Dimension W x H x L	EncPad™	FrostGuard™
GS-4.5	ClamShell	16" x 30" x 64"	EP-4.5	N/A
GS-5	ClamShell	24" x 40" x 66"	EP-5	FG-5
GS-6	ClamShell	24" x 40" x 80"	N/A	Consult Factory
GS-7	ClamShell	30" x 48" x 99½"	N/A	Consult Factory
GS-8	ClamShell	38" x 60" x 99½"	N/A	Consult Factory
GS-8.5	ClamShell	38" x 60" x 120"	N/A	Consult Factory

Fabrication & Powder Coat Specifications:

1¼" schedule 40 A.S.T.M. A-53 grade A.E.W. steel framework with 1" x 1" x ⅛" angle iron: ½" #13 gauge diamond pattern rolled expanded metal. Expanded metal die formed for uniformity. All welded construction maximum 4" on center.

State-of-the-art aeronautics industry five step metal cleaning process and iron phosphate solution treatment. Units preheated before applying 2.0-4.0 mil thickness polyester powder to A.S.T.M. D-2794 Impact Resistant and A.S.T.M. D-3359 Adhesive Specifications

Warranty: BPDIGuardShack warranties this product for one (1) year from the date of purchase to be free of defects in material and workmanship. All claims must be made known to BPDIGuardShack in writing within 30 days of the defect becoming known to the purchaser. There are no warranties that extend beyond those described herein, either expressed or implied. BPDIGuardShack reserves the sole right, at it's own option to repair or replace any defective product, and shall exclude any damage caused by accident, misuse or abuse of the product. In no case shall BPDIGuardShack be liable for any incidental or consequential damages what-so-ever.

GUARDSHACK™

www.GuardShackEnclosures.com

800-266-5411