

VANDAL & THEFT RESISTANT ENCLOSURES THAT WORK BEAUTIFULLY



Never any need to install unsightly homemade burlap insulation wrap again. Rugged construction and great UV protection means you can leave **FrostGuard Insulated Blankets** on year round.

The Inexpensive way to protect your backflow assembly from cold weather

- Rugged outer vinyl material has great UV resistance and is now 12% thicker!
- Strong Double Stitched edges.
- Available in **two** standard colors-Forest Green & Woodlands Tan.
- Resilient Industrial Grade R-13 and R-30 Insulation materials can be crushed yet still retain original insulation value and shape.
- A PadLock Grommet is standard equipment to lock your **FrostGuard™ Insulated Blanket** in place.
- Complete and immediate access for testing & servicing.
- Units pay for themselves in the first year in labor savings compared to installing & disassembling other insulation materials.



BACKFLOW PREVENTION DEVICE ENCLOSURES

GUARDSHACK: THE SHAPE OF THINGS TO COME.



FrostGuard™ Insulated Blankets for ½" - 10" Standard and "N" pattern Backflow Assemblies

MODEL # for R-13 MATERIAL	MODEL # for R-30 MATERIAL	INTERNAL DIM. H x L	Use With BPDJ Enc. Model #'s	Popular RP Model Sizing Chart										PVB'S (All Models)
				WATTS			WILKINS			FEBCO				
				009	U009A	909	375	475	975XL	825Y	825YA	860	880	
FG-1-R13	FG-1-R30	22½ X 22	#1	¾	¾-1½				¾-1	¾	1½-2	¾-1	1	1¼-2
FG-2-R13	FG-2-R30	22½ x 30	#2	1-1¼	2	¾-1			1¼-1½	1-1¼		1¼	1¼-2	
FG-3-R13	FG-3-R30	22½ x 40	#3	2		1½			2	2				
FG-3.3-R13	FG-3.3-R30	28½ x 28	#3.3	1-1¼ tall	¾-2 tall	¾-1 tall			1¼-1½ tall	1-1¼ tall	1½-2 tall	1¼-2 tall	1¼-2 tall	½-2 tall
FG-4-R13	FG-4-R30	22½ x 46	#4											
FG-5-R13	FG-5-R30	42 x 74	#5	2½-3		2½-3	2½-4	2½-4	2½-3	2½-3		2½-3		

Multi-Purpose FrostGuard™ Insulated Blankets

MODEL # for MULTI-PURPOSE	INTERNAL DIM. H x L	Popular RP & DC Model Sizing Chart				
		WATTS		FEBCO	WILKINS	
		909/709	6" 774	860/850	375/350	975XL
FG-UN-4	47 X 92	X	X	X	X	X
FG-UN-6	54 X 108	X		X	X	X
FG-UN-8	65 X 125	X		X	X	X

FrostGuard™ Insulated Blankets are an extremely low cost "insurance policy" designed to protect your backflow assembly from the occasional late fall / early spring cold spells which could otherwise result in freeze damage or destruction to exposed backflow assemblies. The **FrostGuard™** also is a "set it and forget it" installation since you can leave it on year round.

FrostGuard™ Specifications

14 oz. vinyl fabric with reinforced double row Machine stitched edges. Standard vinyl colors are Forest Green & Woodland Tan.

Insulation is Industrial Grade, resilient, crushable, compressed fiberglass, available with standard R-values of R-13 and R-30.

Reinforced metal grommets on bottom seam for installation of a padlock.

Any RP relief valve discharge venting is un-impeded, even when bottom seams are padlocked together for best insulation protection



GUARDSHACK ENCLOSURES

A Division of B.P.D.I.

3831 E. Grove St. Phoenix, Az 85040

Phone (602)-426-1002 Fax: (602)-426-1005 1(800) 266-5411

WARRANTY: BPDJ warranties this product for one (1) year from date of purchase to be free of general defects in material and workmanship. All claims must be made known to BPDJ in writing within 30 days of the defect becoming known to the purchaser. There are no warranties that extend beyond those described herein, either expressed or implied. BPDJ reserves the sole right, at its own option, to repair or replace any defective product, and shall exclude any damage caused by accident, misuse or abuse of the product. In no case shall BPDJ be liable for any incidental or consequential damages what-so-ever.